



21xxxS

## Drop Forged C-Clamps, Standard Screw



### PRODUCT DETAILS

- Black threaded screw with T-handle
- Drop-forged and heat treated for maximum strength and greater rigidity
- I-Beam design for extra strength
- Acme threading
- Deep-throat design
- Black oxide finish

### PRODUCT ATTRIBUTES

| Product          |  |  |  |  |  |
|------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>JHW21002S</b> | 2 in                                                                                | 0 in                                                                                | 2-1/8 in                                                                             | .47 in                                                                                | 3,500 lb                                                                              |
| <b>JHW21003S</b> | 3 in                                                                                | 0 in                                                                                | 2-3/8 in                                                                             | .55 in                                                                                | 3,500 lb                                                                              |
| <b>JHW21004S</b> | 4 in                                                                                | 0 in                                                                                | 3-1/4 in                                                                             | .75 in                                                                                | 6,500 lb                                                                              |
| <b>JHW21006S</b> | 6 in                                                                                | 0 in                                                                                | 4-1/4 in                                                                             | .75 in                                                                                | 6,900 lb                                                                              |
| <b>JHW21008S</b> | 8 in                                                                                | 0 in                                                                                | 5 in                                                                                 | .75 in                                                                                | 6,900 lb                                                                              |
| <b>JHW21010S</b> | 10 in                                                                               | 0 in                                                                                | 6 in                                                                                 | .75 in                                                                                | 8,000 lb                                                                              |
| <b>JHW21012S</b> | 12 in                                                                               | 0 in                                                                                | 6-3/8 in                                                                             | .75 in                                                                                | 9,500 lb                                                                              |